



## **CSD**

Public Address - Matrix and IP Systems

Amplifiers-Speakers lines surveillance unit

### **GENERAL FEATURES**

The CSD allows the surveillance of 8 Amplifiers and 8 speaker lines. The system needs the addition of an End of Line element EFL7.

- Microprocessor controlled Surveillance unit
- Amplifier and Speaker lines faults centralization
- Status display on front panel or on PC screen using serial link
- Capacity : 8 amplifiers + 8 speaker lines and 1 standby amplifier
- Double Serial links (DARS and PC)
- Management of switchover to standby amplifier
- Communication with MANXc or PC to display faults Integrated monitoring speaker
- Toggle switch to select the speaker line
- Suitable to integrate sound systems built in full compliance with EN 54-16 standard
- Amplifiers/Speaker lines surveillance unit.
- 8 surveillance terminals capacity.
- Dual technology : DC current and 20KHz detection
- Front panel blue LCD signalling.
- Dry contact Outputs for fault signalling thru relays

### **TECHNICAL CHARACTERISTICS**

<b>Mains Input:</b>	24 V DC
<b>Dimensions:</b>	440x88x240 mm
<b>Weight:</b>	2 Kg
<b>Colours:</b>	Black

### **INSTALLATION**

19" rack mount (2 U)