

## AMH120.5EC - AMH240.5EC

Public Address - Amplifiers and Audio Sources



- 
- Mixer amplifier with 5 inputs, available in 2 powers: AMH120.5EC (120W) & AMH240.5EC (240W)

### GENERAL FEATURES

- 
- 5 inputs with separate volume control
- Mixed or priority mode inputs
- Input 1 overrides all other inputs by remote control
- Input 2 overrides inputs 3, 4, 5 by vox or remote control
- Adjustable levels for Aux 2, 3, 4 and 5
- Bass and treble separate controls
- Phantom power supply for Microphone and 24VDC for paging desk
- Sliding AUX/MIC switches on rear panel
- XLR, RCA, and plug-in screw connectors for inputs
- 0dB output on RCA connector
- 50V- 70V -100V line outputs using press connector
- Led VU-meter
- Protection against overload and short circuits
- Easy configuration
- Smaller size
- High reliability
- High quality connectors
- Specific options
- Multichannel amplifiers in 2U cabinet
- Compliance : EN6065, CEM, RoHs
- Measurement as per IEC-268-3 Standard

### TECHNICAL CHARACTERISTICS

|                            |                                       |
|----------------------------|---------------------------------------|
| <b>Inputs:</b>             | 5                                     |
| <b>Power:</b>              | 120 W (AMH120.5EC), 240W (AMH240.5EC) |
| <b>Loudspeaker Output:</b> | 100 - 70 - 50 V                       |
| <b>Mains Input:</b>        | 230 V AC                              |
| <b>Dimensions:</b>         | 440 x 88 x 283 mm                     |
| <b>Weight:</b>             | 11 Kg (120W) - 17 Kg (240W)           |
| <b>Colours:</b>            | Black                                 |

### INSTALLATION

Rack mount (2U) or stand alone