



## P5556

Public Address - Microphones and Call Consoles

Desk withm general call until 6 zones.  
With PL9606

### GENERAL FEATURES

- 'All' push button of General Call, and LED indicating hold (red) during the broadcast of the notice.
- Led (green) indicating connected microphone.
- 'Lock' push button for locking general call.
- Push buttons for calls to areas.
- 'On/off' switch for DING-DONG, with led indicating status.
- Front adjustment for level of broadcast of notices.
- Reset internal protection (Polyswitch) against short-circuits and inversion of supply polarity.
- 2 DB1 and DB2 rear connectors (type DB15) to allow an easy and quick connection to Sonelco line.
- Rear jack for supply with an external auxiliary supplier 15V/1A.
- Auxiliary audio exit of a Jack 6.35 type.
- Internal pre-adjusted adjustments from the factory for Ding-dong level and microphone sensibility.

### TECHNICAL CHARACTERISTICS

<b>Output Impedance:</b>	100 Ohm.
<b>Sensitivity:</b>	5mV/1PSA
<b>Nominal Input Level for Warning Switching:</b>	$V(Z_i) = 15 \text{ V} / I_{\text{max}}: 500 \text{ mA}$
<b>Nominal Output Level for Calls:</b>	3 Vrms
<b>Maximum Consumption:</b>	500 mA
<b>Standby Consumption:</b>	25 mA
<b>Dimensions:</b>	85x150x150 mm
<b>Colours:</b>	P5556-02 (Graphitie)

### INSTALLATION