

CSD

Public Address - Matrix and IP Systems

Amplifiers-Speakers lines surveillance unit

GENERAL FEATURES

The CSD allows the surveillance of 8 Amplifiers and 8 speaker lines. The sytem needs the addition of an End of Line element EFL7.

- Microprocessor controlled Surveillance unit
- Amplifier and Speaker lines faults centralization
- Status display on front panel or on PC screen using serial link
- Capacity : 8 amplifiers + 8 speaker lines and 1standby amplifier
- Double Serial links (DARS and PC)
- Management of switchover to standby amplifier
- Communication with MANXc or PC to display faults Integrated monitoring speaker
- Toggle switch to select the speaker line
- Suitable to integrate sound systems built in full compliance with EN 54-16 standard
- Amplifiers/Speaker lines surveillance unit.
- 8 surveillance terminals capacity.
- Dual technology : DC current and 20KHz détection
- Front panel blue LCD signalling.
- Dry contcat Outputs for fault signalling thru relays

TECHNICAL CHARACTERISTICS

Mains Input:	24 V DC
Dimensions:	440x88x240 mm
Weight:	2 Kg
Colours:	Black

INSTALLATION

19" rack mount (2 U)

These features given for information only. Sonelco.com reserve the right to make changes without notice in order to improve the product. More information: (+34) 976 259 135 / (+34) 609 719 454 / sat@sonelco.com