



P5580

Public Address - Microphones and Call Consoles

Desk for notification broadcast with general call, 18 areas and DIN-DON.

GENERAL FEATURES

- 'All' push button of General Call, and LED indicating hold (red) during the broadcast of the notice.
- Led (green) indicating connected microphone.
- 'Lock' push button for locking general call.
- Push buttons for calls to areas.
- 'On/off' switch for DING-DONG, with led indicating status.
- Front adjustment for level of broadcast of notices.
- Reset internal protection (Polyswitch) against short-circuits and inversion of supply polarity.
- 2 DB1 and DB2 rear connectors (type DB15) to allow an easy and quick connection to Sonelco line.
- Rear jack for supply with an external auxiliary supplier 15V/1A.
- Auxiliary audio exit of a Jack 6.35 type.
- Internal pre-adjusted adjustments from the factory for Ding-dong level and microphone sensibility.

TECHNICAL CHARACTERISTICS

Output Impedance:	100 Ohm.
Sensitivity:	5mV/1PSA
Nominal Input Level for Warning Switching:	$V(Z_i) = 15\text{ V} / I_{\text{max}}: 500\text{ mA}$
Nominal Output Level for Calls:	3 Vrms
Maximum Consumption:	500 mA
Standby Consumption:	25 mA
Dimensions:	85x150x150 mm

INSTALLATION